

DS-2CE56C2T-IR Datasheet

Check its price: [Click Here](#)

Overview

Hikvision DS-2CE56C2T-IR is the HD720P IR Turret Camera.

Quick Spec

Table 1 shows the quick spec.

Model	DS-2CE56C2T-IR
Image Sensor	1.3MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	1280(H)x960(V)
Min. Illumination	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	3.6mm (2.8mm, 6mm optional) Angle of View: 78°(3.6mm), 97.3°(2.8mm), 51.2°(6mm)
Lens Mount	M12
Adjustment Range	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day& Night	IR cut filter with auto switch
Video Frame Rate	720p@25fps/720p@30fps
HD Video Output	1 Analog HD output
Synchronization	Internal Synchronization
S/N Ratio	More than 62 dB

Product Details

Hikvision DS-2CE56C2T-IR provides these key features:

- 1.3 Megapixel high-performance CMOS
- Analog HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance
- IP66 weatherproof

Compare to Similar Item

Table 2 shows the comparison.

Model	DS-2CE18U8T-IT3	DS-2CE56C2T-IR
Image Sensor	8.29 MP high performance CMOS	1.3MP CMOS Image Sensor
Effective Pixels	3840 (H) × 2160 (V)	1280(H)x960(V)

Shutter Time	PAL: 1/12.5 s to 1/10,000 s NTSC: 1/15 s to 1/10,000 s	1/25(1/30) s to 1/50,000 s
Day& Night	IR cut filter with auto switch	IR cut filter with auto switch

Get More Information

Do you have any question about the DS-2CE56C2T-IR?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

DS-2CE56C2T-IR Specification	
Camera	
Image Sensor	1.3MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	1280(H)x960(V)
Min. Illumination	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	3.6mm (2.8mm, 6mm optional) Angle of View: 78°(3.6mm), 97.3°(2.8mm), 51.2°(6mm)
Lens Mount	M12
Adjustment Range	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day& Night	IR cut filter with auto switch
Video Frame Rate	720p@25fps/720p@30fps
HD Video Output	1 Analog HD output
Synchronization	Internal Synchronization
S/N Ratio	More than 62 dB
General	
Operating Conditions	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 4W
Weather Proof	IP66
IR Range	Up to 20m
Dimension	Φ89.5 × 69.8 mm(Φ3.52" × 2.75")

Contact Us

Want to buy this series of products? please contact us:

- Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com

Order Now

GO to buy this product: <https://www.router-switch.com/ds-2ce56c2t-ir.html>