

[Get a Quote](#)

Overview

WS-C2960G-8TC-L is one of the Cisco Catalyst 2960G Series switches. It provides 8 Ethernet 10/100 ports and 1 dual-purpose uplink (dual-purpose uplink port has 1 10/100/1000 Ethernet port, 1 SFP-based Gigabit Ethernet port, 1 port active).

Quick Specs

Figure 1 shows the appearance of the WS-C2960-8TC-L.




Table 1 shows the Quick Spec of the WS-C2960-8TC-L.

Product Code	WS-C2960-8TC-L
Enclosure Type	Rack-mountable - 1U
Feature Set	LAN Base
Uplink Interfaces	1 dual-purpose (10/100/1000 or SFP) ports
Ports	8 x 10/100 ports
Throughput	2.7 Mpps
Backplane Capacity	16 Gbps
DRAM	64 MB
Dimensions	1.73 x 10.6 x 6.4 in.
Package Weight	4 Kg

Product Details

Figure 2 shows the front panel of the WS-C2960-8TC-L.



Note:

(1)	System LEDs
(2)	Mode Button
(3)	Console port
(4)	8 × 10/100 ports
(5)	Dual-purpose port

Figure 3 shows the back panel of the WS-C2960-8TC-L.



Note: There are a AC power connector on the back panel. WS-C2960-8TC-L has no fan.

The Accessories

Table 2 shows some accessories of the WS-C2960-8TC-L.

Models	Description
GLC-LH-SM	GE SFP, LC connector LX/LH transceiver
GLC-SX-MMD	1000BASE-SX SFP transceiver module, MMF, 850nm, DOM
CAB-CONSOLE-RJ45	Console Cable 6ft with RJ45 and DB9F

Compare to Similar Items

Table 3 shows the comparison of similar items.

Models	WS-C2960-8TC-L	WS-C2960C-8TC-L
--------	----------------	---------------------------------

Ports	8 x 10/100 ports	8 x 10/100 Fast Ethernet
Uplinks	1 dual-purpose (10/100/1000 or SFP) ports	2 x 1G copper or 2 x 1G SFP
Feature Set	LAN Base	LAN Base

Get more information

Do you have any question about the WS-C2960-8TC-L?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

WS-C2960-8TC-L Specification	
Type	Fixed
Topology	Ethernet (10/100BaseTX) Ethernet (10/100/1000BaseT) Gigabit Ethernet (SFP)
Maximum Port density	8 10/100 ports
Uplinks	1 dual-purpose (10/100/1000 or SFP) ports
Modular/Expansion Slots	N/A
Architecture	Layer 2 Switching (basic connectivity), Layer 2 Switching (intelligent services), Voice Enabled
Form Factor	Fixed, Rack Mountable, Standalone/Clustering
Dimensions	1.73 x 10.6 x 6.4 in.
DRAM	64 MB
Features	
Specialized Service Modules	N/A
Security	
DHCP Snooping	Yes
Dynamic ARP Inspection	N/A
IP Source Guard	N/A
RP Rate Limiters	N/A
TCP Intercept	N/A
802.1x	Yes
Port Security	Yes
Dynamic VLANs	Yes
Private VLANs	N/A
Private VLAN Edge	Yes
Secure Shell	Yes
SNMPv3	Yes

Unicast RPF	N/A
ACLs (L2-L4)	Yes
Kerberos	Yes
TACACS+	Yes
RADIUS	Yes
High Availability/Resiliency	
Hardware Redundancy	N/A
High Availability/Resiliency	PVST, Broadcast Suppression, Unicast Suppression, Multicast Suppression, Spanning Tree, Portfast, Uplink Fast, Backbone Fast, 802.1s, 802.1w
Management	
Management features	SPAN, RSPAN, CiscoView, Cisco Discover Protocol (CDP), Virtual Trunking Protocol (VTP), Telnet Client, BOOTP, TFTP, CiscoWorks, CWSI, RMON, SNMP, Clustering, Web-Based Management
Scalability	
WAN Interface Support	N/A
Throughput	2.7 Mpps
Backplane Capacity	16 Gbps
Number of VLANs	255

Want to Buy

[Order Now](#)
[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com