IP CCTV-NVR			
مدل	تصوير محصول	توضيحات محصول	قيمت (رياِل)
		IPC-2MP	
DS-2CD1023G2-LIU (2.8mm)	-	Smart Hybrid Light 2 AMP P Builder Camera 1920 X 1000 Republishor - 2 MP resolution/apport Vefor Tempering Alarm Support Motion Detection (Human and vehicle/Supplement Light (R), White Light) Comes with Build-in microphone for real dime suits executify-Outcom Seed (VEO) Support 1 X 555+ VIA 256, X 524+ VIA 264, Compression technology/Support 1 XVIS 4 2000, INI-Comment Play in required for vehicle 110, III 3 Listoid articles Chrome 570, Policy Play in required for vehicle 110, III 3 Listoid articles Chrome 570, Policy Play in required for vehicles (10, III 3 Listoid articles Chrome 570, Policy Play Play in required for vehicles (10, III 3 Listoid articles Chrome 570, Policy Play Play in required for vehicles (10, III 3 Listoid articles Chrome 570, Policy Play	IRR 31,910,000
DS-2CD1123G2-LIU (2.8mm)	9	2 MP Fixed Down Retwork Cumera Higher Start Fixed Fix	IRR 33,310,000
<u>DS-2CD2327G2-L</u> <u>2.8mm</u>		2 MP Color/us Face Turret Network Camera High quality Imaging with 24 Percelution Efficient H265's compression technology Clear imaging against strong back light ext D2 08 WDN technology Focusing on human and wehicle dustification based on deep learning Built-in microphone for real-time audio security(4) 247 rociordin imaging Water and data restaurity(167)	IRR 85,530,000
DS-2CD1123G0E-I		2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CAMDS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30lps - Up to 30 m H range: - 2.6 mm/4 mm/6 mm fixed lens - PoE (Power over Etherned) - 1/265+, H.265-, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECD CASE	IRR 30,050,000
DS-2CD2126G2-ISU 2.8mm		2. MP Auchense Tiend Come Network Camers High cally lim, gaing with 2. MP resolution Dacellers love light performance with powerse by-Dunkfighter technology (Effect) 41.265 - compression technology Chear imaging against storing back light due to 12.08 dit true WDR technology Gouan in human and vehicle dissilization based on deep learning -SU-Built-in microphone for real-time audio security. Audio and alarm interface available Water and duct resistant ((FIG) on audio resistant (EUD)	IRR 85,990,000
DS-2CD2023G2-I	0-	2 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4/6/8 mm fixed lens- Cober 0.01 Ltm @ (F1.2, AGC ON), 0.018 Ltm @ (F1.6, AGC ON), 0 Ltm with IR - H.265+, H.265+, H.265+ -1.2068 WDR-2 Behavior analyses, and face detection - BLC/30 DNR/RDH - PGF 2040 on IR range - Bulls in micro SD/SDHC/SDXC card slot, up to 256 GB	IRR 70,910,000
DS-2CD2027G2-L ColorVu Lite	WEST 23.3	2 MP IR Flaced Bullet Network Camera - 1/2.8° Progressive Scan CMOS - 1920 × 1080/930fps - 2.8/4/6 mm fixed lens - Color- 0.01 Ltux @ (F1-2, AGC ON), 0.018 Ltux @ (F1-6, AGC ON), 0 Ltux with IR - H-265, H-265+ - 12068 WOR - 8LC/3D DNR/RO1- IRG7-Up to-40 m iR range - Bull+ in micro SD/SDNC/SDXC card slot, up to 256 GB	IRR 82,260,000
DS-2CD2025FHWD-I		High quality imaging with 2 MP resolution Excellent low-light performance via powered by Datifighter technology (Hear H.26% compression technology (Hear imaging against stone) back glind due to 120 did true WDR technology (High finame stude tool influstrate innorth movement (Warf and dust resistant (IPPG)) (Robot structure design with finame animaterials.	IRR 82,750,000
<u>DS-2CD2123G2-IU</u>	•	High quality imaging with 2 MP resolution Clear imaging against strong backlight due to 12 06 8 WIR technology (Effect) HL/SES compression technology Built-in microphone for real-time audio security focus on human and whelch targets disatifiation based on deep learning Water and dust resistant (IPEO) and vandal resistant (IREO)	IRR 66,230,000
DS-2CD2H25FWD-IZS	APPOINTS.	2 MP Powered by Darkfighter Varifocal Turret Network Camera High quality maging with 2 MP resolution Excellent lovelight performance via powerby Darkfighter technology Efficient H265 compression technology Clear maging against room pack light due to 20 did true WIDR technology Water and dust resistant (#166) and vandal proof (ELID) Motorized variolal lens for easy installation and monotronig Robust structure design with full metal materials.	IRR 164,010,000
DS-2CD1043G0-I		4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS, 3.0 DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm/s mm fised lens-role (Drawer over Ethernet), 1265, H. 266, H. 264, H. 264, IRS7, Dubl streem, Digital IVER (Wilet Cymaric Range)	IRR 44,720,000
DS-2CD1043G2-LIU		4 MP Smart Hybrid Light Fixed Bullet Network Camera High quality imaging with 4 MP resolution Support Human and Velkine Detection Smart Hybrid Light: advanced technology with hope range Built-in microphose for eadline audio security, Water and dust resistant (IP&T) Efficient H2.5% compression technology Support on-board strange up to \$12.5 (EG) card seldy (Optional)	IRR 48,810,000
DS-2CD1143G0E-I 2.8MM	in our	A MP Fixed Dome Network Camera High-quality imaging with AMP resolution, providing clare and detailed visuals. Efficient H.255- compression technology ensure resolution and surface that storage requirements. 120 GM Vide Dynamic Bange (VIDI) enhances imaging or challenging lighting conditions, offering clar views even with strong bandglings and continuous conditions. Robust construction with IP67 water and dort recurrencements. Equipped with EXR 2.0 behanology for improved infrared performance, allowing for effective monitoring up to 30 meters in low light conditions. Features such a motion detection, video trapering alarma, and a day/hight switch enhance security capabilities. Compatible with multiple streaming protocols and supports various network features for versatile integration into existing systems.	IRR 46,670,000
<u>DS-2CD2347G2-</u> <u>L(2.8mm)</u>	0	High quality imaging with 4 MP resolution Efficient H.265's compression technology Clear imaging against strong backlight onto 130 d8 WIM technology Built on microphone for real-time audio security 4/J Focus on human and velocie target ds. salicitation based on deep learning 24/7 roolonful imaging Water and dast resistant (IPS')	IRR 91,450,000
<u>DS-2CD1143G0-I</u>		4.0 MP IR Network Dome Camera, 1/3* progressive scan CMOS - 30 DNR (Digital Note Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens, Incl. Power over Ethernet), H. 265. + 1, 265. + 1, 264. + 1, 264 1967, IK10. Dual stream, Digital WDR (Wide Dynamic Range)	IRR 48,370,000
DS-2CD1143G2-LIU		4 M9 Smart Hybrid Light Fixed Done Network Camero light quality imaging with 4 MP excludion support Human and White Detection Support Human and White Detection Smart Hybrid Light: advanced technology with long range Bulls in imcorphone for real bulls and such security (Efficient H.265 - compression technology Support on-do-action danage up to \$2.52 (65) card selst) (Optional) Water and dust resistant (IPG7) and vandal resistant (IVX8)	IRR 51,630,000
<u>DS-2CD2046G2-I</u>		A MP Accidence Fixed Mole Bullet Retwork Cumera High Bullet Retwork Cumera High Bullet Winging with AP Persolution Decellent low slight performance with powered by DarkFighter technology Clear Hanging against soring Bucklight due to 20 did to the WDR Exchoology Efficient H.2655 compression technology Florus on human and whick largest clearing tition based on deep learning Bullet in microphone for real-dime auto security (10) Will the microphone for real-dime auto security (10).	IRR 83,790,000

DS-2CD2047G2H-LIU (2.8MM)	-3	4 M/S mart Hybrid Light with Cacro's Fixed Bullet Network Camers Hybrid Statistics I was a server of AM Prescription Smart Hybrid Light Rechnology provides color imaging in low-light conditions (Dear imaging gainst root pe locklight down to 20.08 W/W Six Exchonology Efficient N.25f compression technology reduces bandwidth and stronge usage Focus on human and whole classification based on deep learning algorithms Equipped with an active stroke light and audio alarm for deterrence Provider sent limit executive With belief to the own yeardoo Spoports on-board stronge up to 512 GB via an SD card dot Water and dust resistant (RPCI). Sensing devalphility various venironments	IRR 84,700,000
DS-2CD1743G0-IZ		4.0 MP VF Network Dome Camers-1/3* progressive scan CMOS-30 DNR (Digital Noise Reduction) 2550 x14409;20fps 3 Up to 30 m IR range-2.8 mm to 12 mm manual/motorized (with -PGE (Power over Ethernet)-IP67 H.265+, H.265+, H.264-, H.264- Dual stream-120 dB WDR (Wide Dynamic Range)-2:Motorized VF lens	IRR 85,200,000
DS-2CD2143G2-LIS2U		A MP Audiense Smart Hybrid Light Flaed Dome Network Camera High quality imaging with 4 MP recolution Audiense texticulage from human and verhele collaration based on deep learning Smart Hybrid Smart H	IRR 71,440,000
DS-2CD2T45FWD-I8	6-6	4 MP Powered by Duski glittle Freed Build Network Camera High quality imaging with Per-ecolution Excellent on light performance via powered by Duski glittle stehnology Efficient 14.265 - compression technology Clear imaging against storing back light due to 230 dB true WOR technology Work and dusk resident BIDS Work and dusk resident BIDS	IRR 150,450,000
DS-2CD2143G2-IU		4 MV bundla Blukt- in Mc Fland Done Network Camers High quality imaging with A MP resolution Gear imaging against strong basklight due to 130 dl MVB ethorloogy, Efficient 14.05+ compression technology, Built-in migraphy against strong basklight due to 130 dl MVB ethorloogy, Efficient 14.05+ compression technology, Built-in migraphy against strong basklight due to 130 dl MVB ethorloogy, Efficient 14.05+ compression technology, Built-in migraphy against strong basklight due to 130 dl MVB ethorloogy, Built-in migraphy against strong basklight due to 130 dl MVB ethorloogy MVB ethorloogy against the strong the str	IRR 70,250,000
DS-2CD2T43G2-4LI 4MM		4 MP IR Faxed Builet Network Camera High quality imaging with 4 MP resolution (DSSs 1:320 @30fpx) 4mm fixed less: Celor: Onl. 10 (§12.4, ACCI (DM) 18 Line (§17.4, ACCI (DM) 1	IRR 85,270,000
DS-2CD1T43G2-LIU		High quality imaging with 4 MP resolution Support Human and Vehicle Detection Small Double light desurced technically with long range Bulls in microphone for real-time audio security Water and dust resistant (HSF) Efficient H.255* compression technology Support on-board storage up to 312 GB (Card side) (Optional)	IRR 51,890,000
<u>DS-2CD2T43G2-2I</u> (4mm)		1/3" Progressive Szan CMOS, 2688 x1520@305ps.2.8mm fixed lens - Color- 0.01 Lux @ (£1.2, AGC ON), 0.018 Lux @ (£1.6, AGC ON), 0.018 Lux with IR, H.255-Three streams, 12068 WDR, Focus on human and vehicle targets classification based on deep learning, 8LC/30 DNA/RO1 - 1967 - Built in micro SD/SDNC/2DXC card slot, up to 256 GB-up to 68m IR range	IRR 78,470,000
<u>DS-2CD2443G0-IW</u>		1/3" Progressive Scan CMOS - 2688 × 1520@30fps - IR: 10 m - FIR: 10m - 1208B WDR -Video Compression: H. 265+/H. 265-/H. 264-/H. 364/MJPIGC - Bulli-m Micro SD/DGHC/SDXC Job, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98", vertical FOV: 55" - W: Bulli-m Wi-Fi with WPS	IRR 72,980,000
DS-2CD1357G0-L		5 MP Color/u. Lite Fixed Turnet Network Camera, High quality imaging with 5 MP resolution Excellent low-light performance, Efficient H.26% compression technology, Water and dust resistant (IPG7), 24/7 colorful imaging.	IRR 73,150,000
DS-2CD2163G2-IU (2.8mm)		6 MP Accidence Vandal Fixed Dome Network Camera High quality imaging with 6 MP resolution Clear imaging against storing backglift due to 210 dit true WDR technology Efficient H.255* compression technology Focus on human and whole targetic disaditions based on deep learning Built-in microphone for real-time audio security Water and duct resistant (PIPO) and wonder-installer (PICIO)	IRR 75,120,000
DS-2CD2063G2-I	0-	6 MP IR Fued Bullet Network Camera - 1/2.5° Progressive Scan CMOS - 3072 × 2048@20 Tps - 2.8/4/6/8 mm fixed lens - Color C 0.01 kxt @[17.2, ACC ON], 0.028 kiux @[17.2, ACC ON], 0.028 kiux @[17.2, ACC ON], 0.028 kiux with IR - H.2555 + H.255, H.255, H.2564 + H.2564 - 2 Behavior analyses and face detection - 120dB VIOR - 8LC/3D DNR/ROI - IR67 - Bullit-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 80,810,000
DS-2CD2T67G2H-LI		6 MP Smart Hybrid Light with Coloriu Fixed Bullet Network Camera High quality imaging with 6 MP recolution Smart Hybrid Light: advanced technical with long range Clear imaging against strong back light due to 13 die WM technology Herrich Light: Company to the Colorium technology Flocus on human and vehicle classification based on deep learning Water and dust resistant (WEV)	IRR 141,510,000
DS-2CD2163G2-US2U		6 MP Fixed Dome Network Camera High quality imaging with 6 MP resolution Excellent low-light performance with Cubrivia technology for clear color images, 24/7 Efficient 14,25°s compression technology Clear imaging against strong backlight for 6 to 210 db first w/WR technology	IRR 78,390,000

DS-2CD2T83G2-4I		High quality imaging with 8 MP resolution Efficient N. 265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology	IRR 100.960.000
53-205218362-H		Focusing on human and vehicle classification based on deep learning Focusing on human and vehicle classification based on deep learning Water and dust resistant (IPG7) 4K AcuSerse Varifical Bullet Network Camera, High quality imaging with 8 MP resolution Motorized varifical lens for easy installation and monitoring	TRR 100,500,000
DS-2CD2686G2-IZS		Excellent tow light performance via powered-by-Daskfighter technology (Efficient to Life 5- compression technology) Clear imaging against strong back light due to 120 dB true WDR technology fiscus on human and whole targeted stadification based on deep learning Audio and alarm interface available Water and other restrate ((H64) and varied prior ((H15))	IRR 192,250,000
DS-2CD2783G2-IZS		8 MP(4G) IR Vari-focal Done Network Camera - 1/2.5° Progressive Scan CMOS - 48ax IR distance: 30 meters - 28 to 12 mm varifocal lens - Color- 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.8, AGC DN) (Lux with Hr. 14.25° x 14.56, 1.246° x 14.25° x 14	IRR 144,760,000
DS-2CD2786G2-IZS	2011002	48 Acufense Varidocal Dome Network Camera, High quality imaging with 8 MP resolution Motorized varional lens for easy installation and monotroning. Excellent low-light performance via powered by DasKighter technology Clean Hard V-26F- compression technology Clean Imaging Image V-26F- compression technology Focus on human and vehicle target dissulfication based on deep learning Audio and alam interface available. Water and dest-resistant (PRG) and andral proof (K10)	IRR 215,890,000
DS-2CD2083G2-I	0-	8 MP IR Faxed Buillet Network Camers - 1/2.8" Progressive Scan CMDS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 los @(11.2, AGC ON), 0.028 los @(9/2.2, AGC ON), 0.02 los with IR - H-265+, Up to 40 m IR range - 2 Behavior analyses and face detection - 1008 WPR - BL/(2D ONR/RO/)+IC - P67 - Built-in micro SO/SON-C/SOXC card slot, up to 256 GB	IRR 83,360,000
DS-2CD2085G1-L		4K Powered by Darki'ghter Fixed Mini Bullet Network Camera High quality manging with 8 MP recolution Excellent lovelify beforemance via power by Darki'ghter technology Efficient H.255'- compression technology Clear imaging against room pack sight due to 210 did tru WIDR technology Water and out resistant (IP67) Robust structure design with fine fined imaterial.	IRR 108,600,000
DS-2CD2086G2-I		AK Audzense Flased Mini Bullet Network Camera High Gualptiv Janging with SA Percedution Excellent low light performance via powered by PubArighter technology Efficient 12.65° compression technology Clear maping against storag back light due to 210 dB true WDR technology Focus on human and whole target dis salization based on deep learning Built-in microphone for real-time audio security(u) Water and date resistant (IPS7)	IRR 116,990,000
<u>DS-2CD2183G2-IU</u>		8 MP IR Fixed Dome Network Camera - BL/2/B DNR/RO1 - PE/J, IKIO - Bull-in micro SD/SDHC/SDNC card slot, up to 256 GB- 1/2-8° Progressive Scan CAMDS - 3840 o 215(B ± 2.84) mm fixed fero: -Color: 0.01 ka @(F1.2, AGC DN), 0.028 ka @(F2.0, AGC DN), 0 ka with IR - H.265+ 2 Behavior analyses and detection - 120d8 WDR - Bull-in microphone, Up to 30 m IR range	IRR 79,120,000
DS-2CD2185FWD-I		Alf Sind Dorne Network Carriers High quality imaging with AP rendefines, filtered + 1.50+ compression technology Cher imaging against strong back light due to 2.0 did true WDR technology See de Construction of the Construction	IRR 112,050,000
DS-2CD1T83G0-I	B - 🔊	Af Fixed State Network Camers High audity Imaging with \$4 Mericantion Gear imaging against strong back light due to 12 Od MVS technology (files imaging against strong back light due to 12 Od MVS technology (files imaging against strong back light due to 12 Od MVS technology Water and dustresistant ((IMF)) Easy installations with Power over files (IMF) schoology (MVS audity of the Common of the Comm	IRR 76,340,000
DS-2DE4225W-DE-T5		2MP 25+ Network IR Speed Dome - 1/2.8° progressive scan CMOSUp to 1920 = 1080@305ps resolution-Min. Illumination: Color-0.005 Lux @151.6, AGC ONB, BVM-0.001 Lux @151.6, AGC OND Lux with IR25+ optical zoom Focal Length 4.8 mm to 120 mm - 16+ digital zoom - WDR, HLC, BLC, 3D DNR, Defing, BIS, Regional Exposure, Regional Focas - Up to 100 m IR distance - 12 VOC & Rv4+ (802.3 av, class)s) Support H.165+(H-126) video compression—Excellent low-light performance with proceedings of the Color of the Co	IRR 244,210,000
DS-2DE4425W-DE-T5		4MP 25 × Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 2560 × 1440@30fps resolution-Min. Illumination: Cobr. 0065 Lue (8°15.4,66C ON), BWC.0001 Lue (8°16.4,66C ON), Dut with IR25 votical zoom Focal length 4.8 mm to 120 mm - 156 (eight anno - WDA), Hit., Bit., 20 D DNR, Pedie, Bit., Sepical Esposure, Regional Focar-up to 106 in distance - 12 VDC & PoE+ (802.3 at, class4). Support H 156*/H-165 video compression: Excellent low-light performance with proceedings of the 106 of 106 in 166	IRR 275,290,000
DS-2SE4C225MWG-E		Captures a large area and great details at the same time High quality imaging with 2 life control of the contr	IRR 340,540,000
	40	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H 265+/H 265/H 264+/H 264 - Incoming bandwidth : 40	
DS-7604NI-K1		Mbps - HDMI output: 4K (840 × 2160)/304te - Capacity : 1 SATA interface Up to 6TB capacity Mbps - HDMI output: 4K (840 × 2160)/304te - Capacity : 1 SATA interface Up to 6TB capacity	IRR 62,710,000
DS-7608NI-K1		IP video input: 8-ch Up to 8 MP resolution - Decoding format: H.265+/H.265+/H.264+/H.264-Incoming bandwidth: 80 Mbps-HDMI output: 4K (3840 × 2160)/30Hz - Capacity: 1 SATA interface Up to 6TB capacity	IRR 68,540,000
<u>DS-7616NXI-K2</u>		16-th 10 K simis AnoSemu 48 K NR Up to 16-d Pile Camera Imposts H 1255-/H 1256/H 2354-/H 1256 V video formats Up to 2-th-91 1266 Pile Sim Or of-th-91 48 V or 12-th-91 1080 pile decoding capacity Up to 150 Mbgs incoming bandwidth Advised Militarium Anomesen technologicum incomining handwidth Advised Militarium Anomesen technologicum incomining handwidth Advised Militarium Anomesen technologicum incomining handwidth	IRR 100,610,000
<u>DS-7732NXI-K4</u>	0	Up to 3.2-th Discurses liquids. 14.254-h.126(A).1264-h.146-h.146-th Commits Up to 2-cheg12 MP or 3-cheg8 MP or 6-cheg8 MP or 12-cheg1080p decoding capacity Up to 3.5-dheg8 MP or 14-cheg8 MP or 12-cheg8 MP or 12-cheg1080p decoding capacity Up to 3.5-dheg8 more immitted manual effort and security costs Adopt Hibridion Acusers between Up or 12-cheg8 MP or 12-che	IRR 267,160,000
DS-9632NXI-I8/S		32-6-3 24.6 Academic NVB N356-9-1-3 (ASA) ASA (Asa Ask Asa Remails Intelligent assaying based on drep learning algorith Up to 1-ch facial recognition for video stream, or up to 4-ch plantime strengthing for face picture Up to 1-ch facial recognition for video stream, or up to 4-ch facial recognition for face picture Up to 1-ch facial recognition for video stream or up to 4-ch facial recognition for face picture Up to 1-ch 300 degree (as planting) Up to 12-0 blogs incoming provisions Up to 1-ch 300 blogs incoming provisions Up to 1-ch 300 blogs incoming provisions	IRR 719,260,000
IDS-9632NXI-I8/4F		Facial Recognition and Companions - Tean Peture Liberry, 15 (Inburies, 100,000 Petures) Face Contrar Analysis, Costandation and Comparison and Alam, 4-61 Face Petures Companion Alam, Alam Insinger Actions. Recording, Audio Warming, Rotify Surrellistace Center, Send E-mail Tace Peture Search, False Alam Filtering Up to 32 Channel IP Voto Inputs, Hormonig Bandwicht 2500 Mbps Faccoding Resolution up to 12 Min - Synchronous 2-ch 10MM, 2-ch VGA and Hormonia Act (1880 x 2016) Resolution H. 165 (74) LSS(H. 126-4H. 126-MPHES, 546-Audioptive Video Formatting HIGD Hot Sheep With AROU, RADIO, RADIO, RADIO, RADIO Storage HIGD Hot Sheep With AROU, RADIO, RADIO, RADIO, RADIO Storage 156 Alam Inputs, Chappers, 1 Audio Output	IRR 3,795,830,000
	در آرتباط باشید	برای اطلاع از موجودی و قیمت سایر محصولات با همکاران ما در بخش فروش	

021-88529107 - 021-86047721